Image not found or type unknown

Decorative square sconce with indirect light from the Eclipse TROLL family.

DESCRIPTION

Decorative square sconce with indirect light from the Eclipse TROLL family setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used in passing areas, entrances, staircases or similar areas. Luminaire has been designed for wall surface mounting. Luminaire body made of aluminium finished in white. Luminaire sets a 12 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 1328 Lm, with an efficiency of 88,8 Lm/W and a total consumption of 15 W. The average life for the luminaire is 50000 h (established at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OF fed at 220-240V; 50/60 Hz.

Item code	**11.1914.4301.33**
Product type	**Indoor Lighting**
Category	**Wall Luminaires**
Family	**Eclipse**
Subfamily	**Eclipse Square**
Materials	**Luminaire body made of aluminium finished in white.**
Installation instructions	**Luminaire has been designed for wall surface mounting.**
Pictograms	

Dimensions	
Product dimensions (mm)	**250 x 250 x 40**
Packing dimensions (mm)	**260 x 260 x 50**
Net weight (g)	**638**
Gross weight (Kg)	**0,73**

Scheme

Scheme



Product	
Real power (W)	**15**
Real luminous flux (Lm)	**1328**
Luminous efficiency (Lm/W)	**88,5**
Life time (h)	**50000**
IP	**20**
Electrical class insulation	**Class 1**
Operating temperature	**from -20°C to 35°C**
Electrical feeding	**220..240V, 50/60Hz**
Colour (RAL)	**White**
Energy efficiency class	**A+**

Control gear	
Control gear included	**Yes**
Control gear	**Electronic Control Gear**
Power Factor	**0,9**

Light source	
Light source included	**Yes**
Light source	**Led**
Nominal power (W)	**12**
Nominal luminous flux (Lm)	**1700**
Colour temperature (K)	**3000**
Colour consistency (SDCM)	**3**
CRI	**80**

Photometry

Photometry